



命名规则	NZ	-	M4	-	1.5	-	ZU
	NZ	-	S	-	M4	-	X
	↓	↓	↓	↓	↓	↓	↓
	产品类型	材料代码	螺纹代码	尾缀代码	表面处理类型		

所有尺寸：毫米

螺纹规格	规格型号		螺纹代号	尾缀代码	A +0.15/ -0.05	适用 最佳板厚	板孔直径 +0.08/-0	C +0/-0.13	E +/-0.15	T +/-0.13	孔中心 距自由边 最小距离
	碳钢	不锈钢									
M4 × 0.7	NZ	NZS	M4	1.5	1.5	1.5	6.0	5.98	7.0	4.0	6.9
				2.0	2.0	2.0					
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
M5 × 0.8	NZ	NZS	M5	1.5	1.5	1.5	8.0	7.98	9.0	5.0	7.1
				2.0	2.0	2.0					
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
M6 × 1.0	NZ	NZS	M6	2.0	2.0	2.0	9.0	8.98	10.0	6.0	8.6
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
				6.0	6.0	6.0					
				8.0	8.0	8.0					
				10.0	10.0	10.0					
M8 × 1.25	NZ	NZS	M8	2.0	2.0	2.0	11.0	10.98	12.7	6.0	9.7
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
				6.0	6.0	6.0					
				8.0	8.0	8.0					
				10.0	10.0	10.0					
M10 × 1.5	NZ	NZS	M10	2.0	2.0	2.0	13.0	12.98	16.0	7.0	13.5
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
				6.0	6.0	6.0					
				8.0	8.0	8.0					
				10.0	10.0	10.0					
M12 × 1.75	NZ	NZS	M12	2.0	2.0	2.0	16.0	15.95	18.0	8.5	16.5
				2.5	2.5	2.5					
				3.0	3.0	3.0					
				4.0	4.0	4.0					
				5.0	5.0	5.0					
				6.0	6.0	6.0					
				8.0	8.0	8.0					
				10.0	10.0	10.0					

公制螺纹