



所有尺寸：毫米

公制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± 0.4 (长度单位为毫米)										最小 板厚	板开口 尺寸 +0.08	H ± 0.4	S 最大值	T 最大值	孔中心到 板边缘的 最小距离
		螺钉材料			6	8	10	12	15	18	20	25	-	-						
		碳钢	不 锈钢																	
M3x0.5	TFH	TFHS	M3	6	8	10	12	15	18	20	25	-	-	0.51	3.0	4.5	1.8	0.64	5.6	
M4x0.7	TFH	TFHS	M4	-	8	10	12	15	18	20	25	30	35	0.51	4.0	5.8	1.8	0.64	7.2	
M5x0.8	TFH	TFHS	M5	-	8	10	12	15	18	20	25	30	35	0.51	5.0	6.4	2.3	0.64	7.2	

所有尺寸：英寸

英制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± 0.015 (长度=长度编码/16英寸)										最小 板厚	板开口 尺寸 +0.003 -0.000	H ± .015	S 最大值	T 最大值	孔中心与 安装板边缘 最小距离
		螺钉材料			.250	.312	.375	.500	.625	.750	.875	1.000	1.250	1.500						
		碳钢	不 锈钢																	
.086-56 (#2-56)	TFH	TFHS	256	4	5	6	8	10	12	-	-	-	-	.02	.085	.141	.070	.025	.187	
.112-40 (#4-40)	TFH	TFHS	440	4	5	6	8	10	12	14	-	-	-	.02	.111	.176	.070	.025	.219	
.138-32 (#6-32)	TFH	TFHS	632	4	5	6	8	10	12	14	16	20	24	.02	.137	.203	.070	.025	.250	
.164-32 (#8-32)	TFH	TFHS	832	4	5	6	8	10	12	14	16	20	24	.02	.163	.234	.070	.025	.281	
.190-24 (#10-24)	TFH	TFHS	024	-	5	6	8	10	12	14	16	20	24	.02	.189	.250	.090	.025	.281	
.190-32 (#10-32)	TFH	TFHS	032	-	5	6	8	10	12	14	16	20	24	.02	.189	.250	.090	.025	.281	