



命名规则	FM	-	K	-	S	-	B	-	M6	-	15	-	ZU
	↓ 头型 代码		↓ 柱体 代码		↓ 材料 代码		↓ 盲孔		↓ 螺纹 代码		↓ 长度 代码		↓ 表面处 理类型
	FM 平头		-- 光滑圆杆		-- 碳 钢								ZU 蓝锌
	SM 小头		K 直纹圆杆		S 不锈 钢								ZC 彩锌
	CM 沉头		H 半 六角		A 铝合 金								X 钝化
			HH 全 六角										

所有尺寸：毫米

公制螺纹	螺纹规格	型号规格			螺纹代码	头部形状	杆部形状	通盲孔	铆接厚度 e	安装孔 Do +0.15/ +0.05	杆径 D -0.03/ -0.10	头径 dk +/-0.5	头厚 K	总长 L Max	铆后长度 (参考) h Ref.
		螺母材料													
		碳钢	不锈钢	铝合金											
M3x0.5	FM	FMS	FMA	M3	平头	光杆直纹	通孔	0.5-1.0	5.0	5.0	7.0	0.8	8.8	5.8	
	FMK	FMKS	FMKA												
M4x0.7	FM	FMS	FMA	M4	平头	光杆直纹	通孔	0.5-1.0	6.0	6.0	9.0	0.8	10.0	7.5	
	FMK	FMKS	FMKA												
M5x0.8	FM	FMS	FMA	M5	平头	光杆直纹	通孔	0.5-1.0	7.0	7.0	10.0	1.0	12.0	9.3	
	FMK	FMKS	FMKA												
M6x1.0	FM	FMS	FMA	M6	平头	光杆直纹	通孔	0.5-1.5	9.0	9.0	13.0	1.5	15.0	11.0	
	FMK	FMKS	FMKA												
M8x1.25	FM	FMS	FMA	M8	平头	光杆直纹	通孔	0.5-1.5	11.0	11.0	15.0	1.5	17.0	12.3	
	FMK	FMKS	FMKA												
M10x1.5	FM	FMS	FMA	M10	平头	光杆直纹	通孔	0.5-1.5	13.0	13.0	17.0	1.8	20.5	15.0	
	FMK	FMKS	FMKA												